

Date:

Comments:

Project:



Gantom ONE UP



Gantom One UP Beam Control Accessories



Gantom ONE UP with Hex Louver

Product Model

- GC278B - Gantom ONE UP - RJ45
- GP278B - Gantom ONE UP - Pro Cable

Features

- RGBW color-mixing spotlight
- Tight and punchy native 4.5 degree beam
- Control via DMX512
- Internal constant current driver gives highly efficient and consistent output.
- Compact form factor and included yoke allow for easy and discrete installation.

Description

Building off the success of the Gantom One, the One UP brings four-color output to this LED pin spot and delivers a tight and punchy beam that produces homogeneous color mixing, even at close distances. Featuring a 4.5 degree beam angle, the Gantom One Up includes 4 diffusion filters, hex louver, and optional top hat, half hat, and angled cowlings for easy control over the beam. Its native DMX control and balanced dimming curve make it perfect for even the most demanding of lighting designers.

Applications

- Themed entertainment
- Dark rides
- Restaurants
- Museums
- Retail
- Theater and stage
- Trade shows

Optional Components

Accessories

| | |
|-------|--|
| FA44 | Top Hat for Gantom One and Gantom 7 "B" models |
| FA45 | Half Hat for Gantom One and Gantom 7 "B" models |
| FA46 | Angled Cowling for Gantom One and Gantom 7 "B" models |
| FA47 | Ingress Protection Kit for Gantom One, One Up, and 7 "B" models |
| RP34 | Diffuser Pack for Gantom One, Gantom 7, and Gantom One Up "B" Models |
| TL300 | Pro Cable Track Adapter for Stucchi EVO Track |
| TL301 | RJ45 Track Adapter for Stucchi EVO Track |

Technical Specifications

Physical

| | |
|-----------|----------------------------|
| Material | Black Anodized Aluminum |
| IP rating | IP65 |
| | IP67 - With FA47 Installed |
| Weight | 308 grams (10.86 oz) |

Electrical

| | |
|-----------|-------------------------------------|
| Voltage | 12-24V DC |
| Power | 6.5W |
| Dimming | DMX |
| Connector | GC278B - RJ45 GP278B - Pro Cable |

Thermal

| | |
|-------------------------------|---------------------|
| Ambient operating temperature | 0-50° C (32-122° F) |
| Cooling method | Passive |

Certifications

| | |
|--------------|----------|
| USA / Canada | UL |
| Europe | CE, RoHS |

Photometrics at Full Power

| | Beam/Field Angle | 1m Illuminance (3.3ft) | 2m Illuminance (6.6ft) | 3m Illuminance (9.8ft) |
|---------------|------------------|------------------------|------------------------|------------------------|
| Gantom ONE UP | 4.5° / 12.7° | 1603 lx (149 fc) | 400.75 lx (37 fc) | 178.11 lx (16.5 fc) |

DMX

| | |
|-------------------|--------------------|
| Channel footprint | 4 |
| Addressing | DarkBox Programmer |
| Lowest dimming | 0.05% |

DMX Mapping

| | |
|-------------|---------------------------|
| RGBW: CH. 1 | Red Intensity (0%-100%) |
| RGBW: CH. 2 | Green Intensity (0%-100%) |
| RGBW: CH. 3 | Blue Intensity (0%-100%) |
| RGBW: CH. 4 | White Intensity (0%-100%) |

LED color

| | |
|------|--|
| RGBW | Red 625nm, Green 530nm, Blue 460nm, White 6000K |
|------|--|

Warranty

| | |
|---------|---------|
| Fixture | 2 Years |
|---------|---------|

Gantom One UP

4 Color Narrow Beam DMX Spotlight

